

Indoor LED 1.9 mm 165" FullHD Bundle

NEC LED-FE019i2-165



Essential bundles of brilliance

For bezel-free viewing experiences using vivid LED technology, NEC's FE Series delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, NEC's FE Series provides long lasting NEC quality with industrial-grade power supplies in easy to install, off the shelf bundle solutions for safe operation with minimised downtimes.

Native FHD and UHD resolutions are achieved through configuration of multiple 16:9 cabinets which are bundled with a power bar, framing, mounting and controller.

Either free standing or for seamless integration into interiors, the slim design is sleek and chic as befits the latest innovation in digital content delivery. Benefit from excellent viewing angles, consistent vibrant colours, superb brightness and long lasting performance for meeting rooms and signage applications.

Benefits

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered viewing experience.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with minimal gap necessary due to very low heat emission.

Front serviceable modules – with front access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from NEC's long lasting quality.

Specifications

Product Information

Product Name

NEC LED-FE019i2-165

Product Group

Indoor LED 1.9 mm 165" FullHD Bundle

Order Code

81000188

Display

Pixel Configuration

3-in-1 SMD (Black)

LED type

SMD (1010)

Screen Size [inch/cm]

165 / 419

Aspect Ratio

16:9

Pixel Pitch [mm]

1.9

Brightness (max.) [cd/m²]

700

Lifetime

100000 hrs (50% brightness)

Contrast Ratio (typ.)

5000:1

Viewing Angle [°]

170 horizontal / 170 vertical

Dimming Capability

256 levels

Colour Processing

16 bit

Colours [Trill.]

281

LED Driving Method

1/30 dynamic scan

Frame Rate [Hz]

50/60

Refresh Rate [Hz]

≤ 3840

Colour Temperature [K]

3000 - 9500

Screen Resolution

Resolution

1920 x 1080

Resolution per m²

277008

Number of Pixel per module [dot]

320 x 180

Number of Pixel per card [dot]

80 x 90

Connectivity

Input Video Digital

1 x 3G SDI; 1 x DVI-D; 1 x HDMI

Input Control

1 x GenLock; 1 x LAN

Electrical

Total Power Consumption [W]

2052 typ. / 4500 max.

Power Consumption typ. [W]

275 per m² (normal use)

Power Consumption max. [W]

600 per m²

Power Consumption typ. [BTU]

935 per m² (normal use)

Power Consumption max. [BTU]

2040 per m²

Environmental Conditions

Operating Temperature [°C]

-20 to 40

Operating Humidity [%]

10 to 80

Mechanical

Dimensions (W x H x D) [mm] per module

608 x 342 x 49

Dimensions (W x H x D) [mm]

3,648 x 2,153.5 x 82

Weight [kg]

390

Additional Features

Shipping Content

1x LED Controller; LED Modules (36 Cabinets, 288 Pixel Cards); Overframe Kit (6x6); Pixel Card Removal Tool; Powerbar (depending on version); Spare Parts Kit; Wall mount (6x6)

Special Characteristics

Cableless Connector for Data and Power; Flush Surface SMD Design; Humidity-proof SMD Design; Single Data Receiving Cards; Single Power Supplies

Manufacturer

NEC

Serviceability

Front Service

IP Level

IP20

Certifications

CCC; CE; ETL; FCC Class A; RoHS

Warranty

3 years

Material

Aluminum Cabinet

* 165 inch



CE



RoHS



FCC Class A

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 08.03.2026