

Laser Projector

# NEC P525UL



## Visible yet noiseless – bringing a sense of calm to your meeting spaces

Scalable visualisation has never been so silent. With an outstandingly low noise level of just 22dB\*, the P525UL is quieter than the ticking of a watch.

Thanks to the completely sealed engine, this laser projector is filter-free meaning 20,000 hours of maintenance-free operation. Comprehensive connectivity and optional WiFi provide the utmost flexibility and time saving operation. The enhanced embedded MultiPresenter functionality enables wireless presentation and screen sharing for up to 16 devices simultaneously, out of the box to your meeting room. The technology is future-proof with the capability of processing 4K inputs at 30Hz. Bringing the future of projection to your meeting room has never been easier, quieter and as low maintenance than with the NEC P525UL.

\*in Eco mode / normal mode: 24 dB / High Bright mode: 27 dB

## Benefits

**No filter service required** – a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.

**Low Noise Level** – with 22dB, the silent technology will not disturb your meeting.

**No lamp replacement** – up to 20,000 h maintenance free operation possible due to Laser Light Source.

**Risk Group 2** – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

**Professional and Flexible Installation** – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

# Specifications

## Product Information

### Product Name

NEC P525UL

### Product Group

Laser Projector

### Order Code

60004708

## Image

### Projection Technology

3LCD Technology

### Native Resolution

1920 x 1200  
(WUXGA)

### Aspect Ratio

16:10

### Contrast Ratio

500000:1

### Brightness

5000 Lumen (approx. 60% in Eco Mode)

### Lamp

Laser Light Source

### Light Source Life [hrs]

20000<sup>1</sup>

### Lens

F= 1.5-2.1, f= 17.2-27.6 mm

### Lens shift

H:±29, V:+60,-0

### Keystone Correction

+/- 30° manual horizontal / +/- 30° manual vertical

### Projection Factor

1.23 – 2 : 1

### Projection Distance [m]

0.8 – 13.5

### Screen Size (diagonal) [cm] / [inch]

Maximum: 762 / 300"; Minimum: 76.2 / 30"

## Zoom

Manual; x1.6

## Focus Adjustment

Manual

## Supported Resolutions

1920x1200 (Maximum resolution of analog input);	3840 x 2160 (Maximum resolution of digital input);	3840x2160 @ 30hz digital
--	---	-----------------------------

## Connectivity

### RGB (analog)

Input: 1 x Mini D-sub 15 pin

### Digital

Input: 1 x HDBaseT; 2 x HDMI™ supporting HDCP

### Audio

Input: 1 x 3.5 mm Stereo Mini Jack for Computer analog; 2 x HDMI audio

Output: 1 x 3.5 mm Stereo Mini Jack (variable)

### Control

Input: 1 x D-Sub 9 pin (RS-232) (male)

### LAN

1 x RJ45; Optional WLAN

### USB

1 x Type B (for Service); 1x Type A (USB 2.0 high speed) with 2.0A Power Supply; 1x Type A (W-LAN Dongle)

### Video Signals

NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

## Remote Control

### Remote Control

Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select

## Electrical

### Power Supply

100-240 V AC; 50 - 60 Hz

### Power Consumption [W]

320 (Normal) / 238 (Eco) / 1.6 (Network Stand-by) / 0.3 (Stand-by)

## Mechanical

### Dimensions (W x H x D) [mm]

480 x 122 x 407 (without lens and feet)

### Weight [kg]

9.7

### Fan Noise [dB (A)]

22 / 24 / 27 (ECO / Normal / High Bright)

### Colour Versions

White

## Environmental Conditions

### Operating Temperature [°C]

5 to 40

### Operating Humidity [%]

20 to 80

### Storage Temperature [°C]

-10 to 50

### Storage Humidity [%]

20 to 80

## Ergonomics

### Safety and Ergonomics

CE; EAC; ErP; RoHS; TUEV Type Approved; TÜV GS

### Speakers [W]

1 x 20 (mono)

## Additional Features

### Special Characteristics

Auto Power ON/OFF; Carbon Savings Meter; Constant Brightness Mode; Control ID Function; DICOM simulation; Direct Power-Off Function; Free Tilt; HDBaseT; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Light Source Adjustment; Magnify; Mouse Control with USB Display; MultiPresenter Function; NaViSet Administrator 2; Optional User Logo; OSD with 30 languages; Password Security System; Plug&Play W-LAN Option; Portrait Setting; Quick Start; Source Select with Beep Function; Test Pattern; Unique Power Saving Functions; USB Viewer; Virtual Remote for direct PC control

## Green Features

### Ecological Materials

Downloadable manuals; ECO packaging

### Ecological Standards

ErP compliant; RoHS compliant

## Warranty

### Projectors

3 years pan-European service

### Light Source

3 years or 10000h (whatever comes first)

## Shipping Content

### Shipping Content

2x AAA Batteries; IR Remote Control (477E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Projector; Quick Setup Guide; Security Sticker; Users Manual; Utility software

## Optional Accessories

### Optional Accessories

Universal Ceiling Mounts (PJ01UCM, PJ02UCMPF); Wireless LAN module (NP05LM2; NP05LM4; NP05LM5)

<sup>1</sup> 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.

\* This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.  
DO NOT LOOK DIRECTLY INTO THE BEAM.



TÜV GS



CE



ErP



RoHS



TUEV Type Approved

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 08.06.2026