

LCD 86" Message Large Format Display

# NEC MultiSync® M861



## Intuitive professional content delivery

Great first impressions can make all the difference; presenting your business in the best possible way will boost your brand. With slim, modern styling, 24/7 operation and high haze panel to reduce reflections when ambient light is high, the M series is the professional way to deliver your message, yet at an attractive price point.

With the optional NEC MediaPlayer or the more powerful Intel® Smart Display Module (Intel® SDM) computing device, you are primed and ready for intuitive signage creation delivering real-time media playback for exceptional visual experiences. For advertising, infotainment and meeting room applications, the M Series provides powerful, upgradable functionality and all the aesthetic appeal to effortlessly reflect your brand credentials.

## Benefits

**Unhindered readability** – no reflections from windows or other light sources means no disruption to the visibility of signage content or meeting room presentation

**Enhanced imaging performance** – advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.

**Mission-critical 24/7 ready operation** – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

**Future Ready Connectivity** – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

**Secure remote management** – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources

# Specifications

## Product Information

### Product Name

NEC MultiSync® M861

### Product Group

LCD 86" Message Large Format Display

### Order Code

L50M861

## Display

### Panel Technology

IPS with Direct LED backlights

### Screen Size [inch/cm]

86 / 217.4

### Aspect Ratio

16:9

### Brightness [cd/m<sup>2</sup>]

500

### Contrast Ratio

≥ 8000:1<sup>1</sup>

### Viewing Angle [°]

178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

### Colour Depth [bn]

1.073 (10bit)

### Colour Gamut

68% of DCI

### Response Time (typ.) [ms]

8

### Panel Refresh Rate [Hz]

60

### Haze Level [%]

Pro (28)

### Supported Orientation

Landscape; Portrait

## Resolution

### Native Resolution

3840 x 2160

## Supported Resolutions

1024 x 768;	1440 x 900;	2560 x 1600;
1280 x 1024;	1600 x 1200;	3840 x 2160;
1280 x 720;	1920 x 1080;	4096 x 2160;
1360 x 768;	1920 x 1200;	7680 x 4320
1366 x 768;	1920 x 2160;	
1400 x 1050;	2560 x 1440;	

## Synchronisation Rate

### Horizontal Frequency [kHz]

15 - 135

### Vertical Frequency [Hz]

23 - 76

## Connectivity

### Input Video Digital

2 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)

### Input Audio Digital

1 x DisplayPort; 2 x HDMI

### Input Control

LAN 100Mbit; remote control wire (3,5mm jack); RS232

### Input Data

1 x USB 2.0 (Downstream); 1 x USB 2.0 (Powered 5V/2A, Firmware Updates); 1 x USB 2.0 Type-B (Downstream)

### Output Video Digital

1 x DisplayPort (loop through: DisplayPort, SDM slot-in PC); 1 x HDMI (loop through: HDMI, SDM slot-in PC); DP (in) to HDMI (out) conversion

### Output Audio Analogue

1 x 3,5 mm jack

### Output Control

1 x LAN 100Mbit

### Input Detect

Custom; First; Last

### PiP/PbP

Dual-Split; Quad-Split; scalable picture size

## Calibration

### Factory Calibration

Gamma; Intensity; RGB; Uniformity; White Point

### Sensor Calibration (through USB)

PC-less Calibration with USB Sensor MDSV Sensor3; White Copy (post self-calibration)

### Calibration with Software

Corner Uniformity; Gamma; Intensity; RGB; Update Factory Calibration; White Point

### Calibration Software

Display Wall Calibrator

## Open Modular Intelligence

### Intel® SDM

accepts Intel® Smart Display Modules Large and Small up to 66 W

### Compute Module Slot

RPi Compute Module 4

## Sensors

### Ambient Light Sensor

Integrated, triggered actions programmable

### Temperature Sensor

Integrated, 3 sensors, triggered actions programmable

## Electrical

### Power Consumption [W]

320 shipping

### Power Savings Mode [W]

< 0.5; < 2 (Networked Standby)

### Power Management

VESA DPMS

### Power Supply

100-240 V AC; 50/60 Hz; internal

## Environmental Conditions

### Operating Temperature [°C]

+0 to +40

### Operating Humidity [%]

20 to 80

### Storage Humidity [%]

10 to 80

### Storage Temperature [°C]

-20 to 60

## Mechanical

### Dimensions (W x H x D) [mm]

1,927.6 x 1,099.1 x 83.2

### Weight [kg]

47

### Bezel Width [mm]

14.3 (left, right and top); 14.8 (bottom)

### VESA Mounting [mm]

4 holes; 600 x 400 (FDMI); M8

### Ingress Protection

IP5x (front); IP2x (back)

### Packaging Dimensions (W x H x D) [mm]

2,090 x 1,225 x 225

### Packaging Weight [kg]

65.1

### Material

Metal

## Available Options

### Accessories

Feet (ST-801); Speaker (SP-RM3); Trolley (L20PNSR780MEU, PD02MHA, PD03MHA); Wall mount (L20PNWALL90EU, SF680P)

## Regulatory

### Safety and Ergonomics

BSMI; CE; EAC; EMC Class B; Energy Star 8; FCC Class B; KC/KCC; PSB; RCM; RoHS; VCCI

### Pixel Failure Class

ISO 9241-307, Class 1

### Resistance to Fire

Metal backcover, plastic material certified acc. to UL94-5VB

## Green Features

### Energy Efficiency

Energy consumption: 193 kWh/1000 h; Energy efficiency class: G; LED backlight

### Ecological Standards

EnergyStar 8.0

## 3rd Party Certifications

### Cisco

Verified for Cisco Collaboration Devices

### Crestron

Certified for Crestron Connected

### Additional Features

#### Special Characteristics

DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo

#### Audio

Integrated Audio Amplifier (for optional speakers up to 2 x 15 W); Integrated Speakers (10 W + 10 W)

#### Shipping Content

2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual

### Warranty

3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension <sup>2</sup>

### Operating Hours

24/7

### External Control

AMX NetLinx Support; ASCII Control Commands; Crestron Connected; HDMI CEC; HTTP Browser; PLink; Scheduled Timer; SNMP

### Remote Management

Automated Email Alerts; NaViSet Administrator 2

### Security

Disable HW Buttons; Disable IR Functionality; Emergency Notification

<sup>1</sup> out of the box conditions, local dimming ON

<sup>2</sup> please refer to terms and conditions of warranty extensions



CE



VCCI



FCC Class B



RCM



RoHS

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 11.04.2026