

Professional Advanced 1DLP Laser Installation Projector

NEC PX2201UL



Advanced performance in compact form

Compact and easily transportable, and yet this large venue projector is packed with advanced technological features. The PX2201UL offers a truly impressive price/ performance ratio delivering superb, richly intense colour through RB laser technology, almost equal in performance to a 3DLP projector. The ultra-bright 20,500 lumen projection can be multiplied using wide interface selection and Edge Blending technology supporting two or more projectors for wider, larger, even brighter images, whilst geometric correction eliminates distortion.

The filter-free optical system protects against dust ingress for performance longevity and minimal maintenance, just as remote adjustment capability means there is no requirement to physically access the projector once its installed. With a low noise level, flexible installation features, SDI interface and 3D support, this innovative projector perfectly services the visualisation needs of higher education and the leisure industry, especially in museums and for mapping.

Benefits

Superb imaging quality – the RB laser technology uses red lasers, increasing the colour gamut to produce more vivid images, unprecedented for single chip DLP projectors, with high light levels supported by a special Brightness Boost Mode.

Maintenance-free performance – the filter-free laser projector uses a special NEC phosphor wheel requiring minimal attention during its lifetime beyond its initial setup.

Hassle-free remote adjustment – motorized lens shift, focus and zoom allows easy and flexible setup without the need for cumbersome physical access to the projector.

Easy handling – its light weight construction (51kg) and robust design means this model is semi-portable making it suitable for flexible applications.

Specifications

Product Information

Product Name

NEC PX2201UL

Product Group

Professional Advanced 1DLP Laser Installation Projector

Order Code

60005581

Image

Projection Technology

1-chip DLP™ Technology

Native Resolution

1920 x 1200
(WUXGA)

Aspect Ratio

16:10

Contrast Ratio

10000:1 with DynamicBlack™

Brightness

20500 Normal / 16400 Lumen Eco; 21500 Centre Lumen;
compliant with ISO21118-2012

Lamp

Laser Light Source

Light Source Life [hrs]

20000¹

Lens

5 optional bayonet lenses

Lens shift

H:-15,+15, V:-50,+50

Keystone Correction

+/- 60° manual horizontal / +/- 40° manual vertical

Projection Factor

depending on lens selection

Projection Distance [m]

0.81 – 84

Screen Size (diagonal) [cm] / [inch]

Maximum: 1,270 / 500"; Minimum: 100 / 40"

Zoom

Motorized

Focus Adjustment

Motorized

Supported Resolutions

1080i/50/60;	480i/50;	720p/50;
1080p/24/25/30/ 50/60;	480p/60;	720p/60
2560 x 1600 (WQXGA);	576i/50;	576p/50;

Connectivity

RGB (analog)

Input: 1 x 5BNC; 1 x Mini D-sub 15 pin
Output: 1 x Mini D-sub 15 pin

Digital

Input: 1 x 3G-SDI; 1 x DisplayPort supporting HDCP; 1 x DVI-D; 1 x HDBaseT; 2 x HDMI™ supporting HDCP
Output: 1 x 3G-SDI

Control

Input: 1 x 3.5 mm Stereo Mini Jack (Wired Remote); 1 x D-Sub 9 pin (RS-232), Ethernet

LAN

1 x RJ45

3D Sync

Output: 1 x BNC IN; 1 x BNC OUT

Video Signals

NTSC; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Input

1 x 3.5 mm Stereo Mini Jack

Output

2 x 3.5 mm Stereo Mini Jack for Screen Trigger

Remote Control

Audio Control; Digital Zoom; Geometric Correction; ID Select; ID set; Power (On-OFF); Select (up, down, left, right); Shutter function; Source Select; Test Picture; Zoom/Focus and Lens Shift Control

Electrical

Power Supply

200-240 V AC; 50 - 60 Hz

Power Consumption [W]

1775 Normal Mode

Mechanical

Dimensions (W x H x D) [mm]

530 x 248 x 745 (without lens and feet)

Weight [kg]

51

Fan Noise [dB (A)]

46 / 48 (Eco / Normal)

Colour Versions

Black

Environmental Conditions

Operating Temperature [°C]

0 to 40

Operating Humidity [%]

0 to 80

Ergonomics

Safety and Ergonomics

CE; EAC; ErP; RoHS

Additional Features

Special Characteristics

3D ready; DICOM simulation; Edge Blending Function; Edge Blending Function (Build In); Free Tilt; Full 3D HDMI Support; Geometric Correction; HDBaseT; LAN; Light Source Adjustment; Manual Wall Color Correction; NaViSet Administrator 2; PJ LINK; Portrait Setting; RS-232 Control

Green Features

Energy Efficiency

Laser light source

Ecological Materials

100% recyclable packaging; Downloadable manuals

Ecological Standards

ErP compliant

Warranty

Projectors

3 years pan-European service

Light Source

3 years or 10000h (whatever comes first)

Shipping Content

Shipping Content

IR Remote Control (RD - 480E); Power Cord; Projector; Quick Setup Guide; Users Manual on CD-ROM

Optional Accessories

Optional Accessories

XpanD 3D Glasses (X105-RFX2); XpanD 3D RF Emitter (AD025-RF-X1)

Lenses

NP45ZL (0.9-1.2:1); NP46ZL (1.2-1.56:1); NP47ZL (1.5-2:1); NP48ZL (2-4:1); NP49ZL (4-7:1)

¹ 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.

* This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG3 of IEC62471-5 Ed1 2015. DO NOT LOOK DIRECTLY INTO THE BEAM.



RoHS



CE



ErP

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.04.2026